SAGITTARIUS

TAPS & SHOWERING

Construction Brass

Dimensions 130mm X 115mm X 25mm

Working pressure HP/LP/COMBI

Parts Pull Indice

Ceramic Lever

Cold valve—15 mm Ceramic disk quarter turn

Hot valve— 15mm Ceramic disk quarter turn

Lever handles, Collar 1/2 nch, Collar 3/4 inch , Flexi

Tails pair 300mm,

Under tap seating O ring 37mm, Pop up rod, Pop up waste assembly , plastic back nut 22mm, brass back

nut, T piece 22mm by 15mm



KE/107/B







Max Flow blend 45°C

0.2 bar	0.3bar	0.5 bar	1 bar	3 bar	
9	11	15	20	22.5	

Max Flow Hot Tap

Max Flow Cold Tap

· · · · · · · · · · · · · · · · · · ·					max rion cold rap				
0.2 bar	0.3bar	0.5 bar	1 bar	3 bar	0.2 bar	0.3bar	0.5 bar	1 bar	3 bar
3.5	5.2	7.5	10	14	3.5	5.1	8	9	15.5

The information contained on this page was correct at the date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances.

We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice