SAGITTARIUS

TAPS & SHOWERING

Construction Brass Body (CuZn40Pb18); Zinc-alloy Han-

dles

Finishes Brushed Nickel

Product Type Contemporary

Water Pressure Min. 0.5 bar, Max. 6.0 bar Tested Between

Plumbing Suitable for all plumbing systems, Hot and

Systems

Cold water pressure preferably balanced
Max. supply pressure differential require-

ment no greater than 5:1

Standards Complies with BS5412, BS EN200

Certification Manufactured to comply with WRAS

Cartridge 1/4 Turn 1/2" Ceramic disc valves

Aerator Spout aerator

Fitting G1/2" BSP Female Flexible inlet connection


hoses

Guarantee 10 years against manufacturing faults

(excluding serviceable parts)

Additional Infor- 360° Swivel Spout

mation



KINETIC MONOBLOC SINK MIXER BRUSHED NICKEL KTS/232/BN





The information contained on this page was correct at the date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances.

We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice

Flow Rates (Litres per minute)

| System Pressure | 0.1 Bar | 0.2 Bar | 0.3 Bar | 0.5 Bar | 1.0 Bar | 1.5 Bar | 2.0 Bar | 3.0 Bar | 4.0 Bar | 5.0 Bar |
|-----------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| | - | 4.0 | - | 6.8 | 9.5 | - | 14.0 | 17.0 | - | - |

